



Standard grease gun, HHFP-DG

connection M 10 x 1

Item number: 12 686 782
EAN: 4103810423352
Discount group: A

technical data

grease gun connection,
pressure-side: M 10 x 1
filling nipple and ventilating valve: M 10 x 1
capacity (cm³): 1000 cm³
loading: 400 g grease cartridge DIN 1284, 500 g grease cartridge, grease gun filling system or bulk grease
diameter of piston (mm): 8 mm
actuation grease piston: manually lever operated
Delivery rate/stroke (cm³): 1,2, at a counter-pressure of 400 bar
Discharge pressure (bar): up to 400 bar
burst pressure (system): 850 bar
burst pressure (grease gun head): 1200 bar
operation of plunger rod: with T-grip
Sealing cover: fixed
wall thickness of grease gun tube (mm): 1,0 mm
colour: graphite-grey
package: polybag, blank
dimensions packaging LxWxH (mm): 600 x 125 x 70
weight including package (kg): 1,65 kg

notes

- operates with greases up to NLGI grade 2.
- plunger with exactly fitting when using bulk grease or cartridge
- Acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 5000 actuating cycles
- Separate filling and ventilation valves on grease gun head
- grease gun head, zinc die casting Z 410
- sure grip handling due to deep band knurls
- The ergonomic handle of the plunger rod assists in overcoming the spring load
- Slip resistant handle on grease gun lever
- Fixed cap, with clamp
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

packaging

Gewicht einschließlich
Verpackung (kg): 1,65 kg
Abmessung LxBxH (mm): 600 x 125 x 70
Packing unit: 1.0