



Hose reel for grease

O-WB-400 bar-DN 6-10 m

Item number: 29 242
EAN: 4103810292422
Discount group: D

Technical data

Length of discharge hose (m): 10
Connection discharge hose: G 1/4" female/male
Length of connecting hose (m): 1
Connection to connecting hose: G 1/4" female/female
Inner diameter of hose (DN): 6
Operating pressure max. (bar): 400
Lacquering
Arm: window grey, satin, RAL 7040
Supporting plate: window grey, satin, RAL 7040
Encasing: blue, Pantone 294 C
Dimensions LxWxH (mm): 472 x 152 x 498
Weight (kg): 16,8

Specification

- Open, for wall/floor mounting
- With hose stop

Notes

- Pressol hose reels are exceedingly robust and are notable for their compact design.
- All metal parts are phosphatized, undercoated and painted.
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting.
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum.
- The hose can be engaged by rotating 1/4 turn

Packaging

Dimensions LxWxH (mm): 540 x 580 x 160
Weight (kg): 17,9
Packing unit: 1.0