



Pneumatikpumpe 3:1, NEF

SRL 860-200/220 l container

Item number: 19 235

EAN:

Discount group: D

technical data

length suction tube: 860
Pressure ratio: 3:1
Max. diameter (mm): 130
Max. air pressure (bar): 10
Min. air pressure (bar): 2
recommended air pressure (bar): 8
cylinder capacity engine cm³: 220
cylinder capacity pump cm³: 70
quantity of strokes at 8 bar at a free-flow (min.): 260
pump capacity at 8 bar at a free-flow (l/min): 22
pump pressure at 8 bar air pressure (bar): 24
air consumption at 8 bar air pressure (l/min): 470
length of discharge pipe work: Depends on size of installation.
Max. suction height: 6 m, suction tube G 3/4"
compressed air connection: G 1/4" female
oil connection - suction side: G 3/4" female
oil connection - delivery side: G 1/2" male
connection container: G 2" male, drum adapter
Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A): 78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A): 77
viscosity of discharged liquid: oil up to SAE 90
classical liquids to be discharged: Engine, gear and hydraulic oil
time duration for 1 complete container draining: 200 l oil in 9 minutes
colour: blue Pantone 294 c
length of engine (mm): 360
weight engine (kg): 3,800

specification

- pneumatic oil pump 3:1
- Does not correspond to German calibration law (NEF).
- Suction tube, G 3/4" male
- for 200/220 l container
- To discharge engine, gear and hydraulic oils
- Ideal for direct connection to pipe lines up to 70 meters. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar)
- Can be easily combined with several hose reels

notes

- Operate pneumatic-pump with maintaining unit 20 218 950

packaging

dimensions LWH (mm): 1310 x 190 x 195
Weight (kg): 8,200
Packing unit: 1.0